



WeConfig

Changelog

Table of Contents

1. WeConfig 2.4.1 Changelog	3
2. WeConfig 2.4 Changelog	4
3. WeConfig 2.3.2 Changelog	6
4. WeConfig 2.3.1 Changelog	7
5. WeConfig 2.3 Changelog	8
6. WeConfig 2.2 Changelog	10
7. WeConfig 2.1.3 Changelog	13
8. WeConfig 2.1.2 Changelog	14
9. WeConfig 2.1.1 Changelog	15
10. WeConfig 2.1 Changelog	16
11. WeConfig 2.0.3 Changelog	20
12. WeConfig 2.0.2 Changelog	21
13. WeConfig 2.0.1 Changelog	22
14. WeConfig 2.0 Changelog	23

1. WeConfig 2.4.1 Changelog

Added

- Theme can now additionally be controlled from the application settings page.

Changed

- Auto-commit toggle has been moved into the application settings page.
- Adjusted the button locations in the Configuration Files page towards the top.

Fixed

- Titlebar can now be properly dragged again.
- Project password dialog is back under file menu.
- Physical network status indicators no longer become detached
- Prevented shell detach when ran from CMD / Powershell on windows
- Corrected the reactivity of the “Apply” button in application settings.

2. WeConfig 2.4 Changelog

Highlights

- Linux! — WeConfig can now be run on both Linux and Windows machines

Changelog

Linux

- WeConfig can now be run on both Linux and Windows machines
- The framework used for the graphical user interface (GUI) has been changed from WPF to Avalonia, with this some parts of the interface has been overhauled
- Windows specific parts of the backend code now also have a corresponding Linux implementation
- .NET has been updated from 9.0 to 10.0

Auto-Commit

- Give the user explicit control over when the new configuration is committed to the device

CLI

- The stand-alone CLI version of WeConfig is now integrated directly into the main version of WeConfig

Device List

- All columns can now be sorted by clicking on the column header
- You can now customize what columns are shown in the device list
- You can now change the order of the columns in the device list
- Auto-Pan now also scrolls in the device list

Discovery

- You can now add accounts pre-discovery if you know there are devices that do not use the default password
- Moved Device Discovery options from below “Means of discovery” into its own tab

Firmware Upgrade

- You can now filter the version list
- Backup is now again a clearly visible, explicit option
- Improved error messages during Firmware Upgrade

Localization

- Support for Spanish

Physical Network

- Merged all the tabs in Physical Network into a single toolbar
- You can now customize what information is shown on the devices in the Physical Network view
- Zoom-to-fill will now linger even when moving devices.

Ping, Traceroute, Max MTU

- You can now use URLs in addition to just an IP Address

UI Changes

- Removed the Backstage menu (the WeConfig-cog that used to be in the top-left corner). You can now find all those features as part of the new File Menu at the top
- CIDR- and IP Address input boxes now preview the generated color of that Address/Range
- Number inputs now show the valid range of inputs (if any)
- Unified all views where you can select and operate a single device to all behave in the same way
- Unified all views where you can select and operate on multiple devices at the same time to all behave in the same way
- Fixed fonts to make sure WeConfig looks the same on both Windows and Linux
- New custom title bar for the application window
- Configuration/Status views now show status accrued for each device during operations.

Device Support

- Add support for the new WeOS 5.30 cli syntax for firewall and port rate-limits
- Added a default SNMPv3 user for Ibex devices
- SNMP Trap and OIDs are now generated from official vendor MIBs, ensuring accuracy and consistency.

Bugfixes

- Resolved an issue where subnets could visually persist even after the final device in that subnet was removed
- Resolved an issue where the yellow warning triangle was difficult to see in light mode
- Resolved an issue where you could not press "Cancel" in the dialog when adding a VLAN-ID
- Improved error messages during Packet Capture
- Improved project serialization stability

3. WeConfig 2.3.2 Changelog

Improvements

- Improved project file compatibility when device metadata is incomplete. Device deserialization now handles missing family/model/firmware fields more gracefully by using safe defaults.
- Expanded firmware background download state handling to include Merlin packages, improving resume/recovery behavior for queued downloads.
- Improved internal device categorization and serializer matching for WeOS 4, WeOS 5, Ibex, Merlin, and XRD devices to make project serialization/deserialization more robust.

Bugfixes

- Fixed an issue where WeOS session handling could miss valid session cookies for WeOS 4.35.0 when devices used alternate SID cookie names.
- Fixed an issue where Factory Reset could report a failure even when the reset had completed, due to prompt/context-path handling in CLI output.
- Fixed aggregate port configuration on WeOS 5 devices by clearing existing members before adding configured ports, preventing stale aggregate membership.
- Fixed an issue where unknown-device project parsing could incorrectly reject certain devices because of partial model data.

4. WeConfig 2.3.1 Changelog

Improvements

- Adjusted project file parsing to be more lenient about malformed port names on WeOS devices, in order to help compatibility with older project files.

Bugfixes

- Fixed an issue where WeConfig would not respect the initial project file argument when launching with a project file
- Fixed an issue where Port Monitoring configuration would stop listening to device selection after the first device de-selection.
- Fixed an issue where Factory Reset would inaccurately report failure when the device was successfully reset.
- Fixed an issue where Port Protection would fail to configure when no alarms were configured on the device.

5. WeConfig 2.3 Changelog

Highlights

- WeConnect Integration — One-click provisioning of WeConnect VPN tunnels on supported devices (WeOS 5), with guided setup, precondition checks, and credential management.
- Unsaved Changes Detection — Automatic monitoring of running vs. startup configuration differences, with commit, revert, and diff viewing per device or across all devices.
- MRP Self-Service licensing — MRP sublicense quota and certificate retrieval via web service for easier license management and auto-provisioning.
- Improved Multi-Device Operations — Configuration changes across FRNT, RSTP, RiCo, MRP, OSPF, RIP, and DSL now use intelligent network-order partitioning for safer parallel operations.

Changelog

WeConnect

- Added WeConnect VPN provisioning with guided setup wizard
- Support for Netcode + OTP and ZIP file credential modes
- Automatic precondition checking (VLAN count, tunnel availability, RIP status, connectivity, clock sync)
- Reinstall, uninstall, and overwrite options for existing WeConnect configurations
- Certificate and key import/delete management for SSL tunnels
- Comprehensive error diagnostics with user-friendly messages

Configuration Management

- Added automatic detection of unsaved configuration changes (running vs. startup)
- Devices with uncommitted changes are now visually indicated (*)
- Added “Commit Running to Startup” and “Revert Running to Startup” actions per device
- Added “Commit All” and “Revert All” bulk actions for all devices with differences between running and startup configurations
- Added diff viewer to compare running and startup configurations side-by-side
- Configuration writes for FRNT, RSTP, RiCo, MRP, OSPF, RIP, and DSL no longer auto-commit to startup — commit is now handled centrally via the unsaved changes system

MRP

- Configuration apply now uses network-order partitioning for safer multi-device operations

Licenses

- MRP Licenses can now be self-serviced via web service for sublicense quota and certificate retrieval, enabling easier license management and auto-provisioning.

Firmware Upgrade

- Upload progress now displays uploaded and total file size (e.g., “3.5 MB / 12.1 MB”) instead of transfer rate

Ping

- Ping tool now accepts hostnames in addition to IP addresses

UI

- Quick action buttons now display tooltips with keyboard shortcut information
- Quick actions are sorted by hotkey for consistency

Bugfixes

- Resolved an SSH timeout issue where certain SSH operation timeouts were not handled, causing missed retries and proxy fallback
- Resolved a memory leak due to excessive amount of uncleaned spinners in the topology.
- Resolved duplicate route entries being generated in the layer 3 routing graph, improving route-mapping performance
- Resolved an issue where VLAN-configuration wasn't done in correct network order
- Resolved an issue where APN configuration on Merlin devices wasn't preserving existing interface names.

6. WeConfig 2.2 Changelog

Highlights

- Support for Merlin devices
 - Discovery, configuration, and firmware upgrade
- New Cellular / APN configuration view for cellular-capable devices
- New Port Monitoring configuration
- New status display for all devices in Device List and Physical Network views.
- Reports extended with DDM values and Layer 1 issues sections

Changelog

Alarm

- Added Media trigger interval support (WeOS 5.27)

Cellular

- WeConfig can now read cellular modem status and signal data from Merlin devices
- Added APN (Access Point Name) configuration

Discovery

- Added mDNS discovery for Merlin devices
- Merlin default SNMP community is now pre-filled when starting discovery

Firmware Upgrade

- Added option to apply “New default” parameters after upgrading devices
- WeConfig can now handle when a single firmware version is composed of multiple files, such as the case with WeOS 5.26+

Ibex

- The login username is now user-configurable
- Default username is automatically updated for firmware versions above 6.9.6-RC0

Merlin Support

- Discovery
- Configuration of:
 - Basic Setup
 - Accounts
 - VLAN configuration
 - SNMP configuration
 - Cellular / APN configuration
- Firmware Upgrade (image1 & image2)
- Backup & Restore (config1)
- Factory Reset
- Status acquisition

Network Template

- Added support for templates with devices that have multiple origin connections
- Added support for retries in network template application
- Improved error messaging for better user feedback on failure

Physical Network

- PC network interface cards (NICs) are now shown as ports on the local PC node
- Routed and one-known-port connections can now be deleted when “Show Connection Info” is toggled.

Port Monitoring

- Added Port Monitoring configuration

Reports

- Added DDM (Digital Diagnostic Monitoring) values section
- Added Layer 1 issues section
- Warning & Critical threshold limits are now shown in more report sections

SNMP Traps

- Trap entries are now color-coded based on severity level

SSH

- Added retry and exponential backoff logic for SSH connection attempts, improving reliability on flaky links.
- Improved handling of unexpected SSH session closures, improving user feedback and general command execution reliability on WeOS devices.
- Improved handling of incoming data through a new channel system.

UI

- Labels and fields that have a tooltip now display a subtle visual hint indicating the presence of additional information

Bugfixes

- Resolved a crash when selecting a device in the Firewall view
- Resolved a crash on apply in FRNT configuration
- Resolved an issue where HSR/PRP stopped loading
- Resolved an issue where HSR/PRP changes were not reflected after applying
- Resolved an issue where FRNT configuration failed to recognise the current topology
- Resolved a crash caused by race conditions in the network model.
- Resolved a crash that occurred when selecting devices in large topologies
- Resolved an issue where Distribute Horizontally / Vertically / Radially did not correctly align large sets of devices
- Resolved an issue where WeOS 4 firmware upgrade presented the bootloader step in the wrong order
- Resolved an issue where VLAN names were used incorrectly in Firewall rules
- Resolved timeout errors in Network Template post-operation handling
- Resolved an issue where removing an Aggregate port did not properly clean up its data
- Resolved an issue where Project Templates did not handle devices with multiple origin connections
- Resolved a VLAN serialization error that could corrupt project files
- Resolved an issue where DDM values were mapped to the wrong ports
- Resolved an issue where connections did not move correctly when merging devices
- Resolved an issue where Ibex device identification could fail after firmware updates

- Resolved a corrupt project file issue caused by Merlin port names
- Resolved a timeout issue with JSON ports on WeOS 5.27.x
- Resolved a typo in the HSR/PRP view
- Resolved an issue where aggregate configuration changes were not applied in the correct network order

7. WeConfig 2.1.3 Changelog

Changelog

Improvements

- Adjusted the radius of “Distribute Radially” to be better aligned with the actual size and centers of the topology nodes.
- Adjusted ring alarm triggers for 5.27.0+ devices to match the updated WeOS behavior where condition is no longer supported.
- Adjusted WeOS 4 Firmware upgrade steps to run in the order bootloader -> primary -> secondary rather than primary -> bootloader -> secondary.

Bugfixes

- Fixed a crash that occurred on rare occasion when deselecting a large number of devices in the topology view.

8. WeConfig 2.1.2 Changelog

Changelog

Improvements

- Added support for labeling FRNT “Broken Ring” SNMP traps.
- Disabled CPU-Bandwidth configuration on WeOS 5.27.0 and later devices, as this feature is no longer supported.

Bugfixes

- Fixed an issue where WeConfig would fail to properly present the RSTP configuration state for certain WeOS4 versions.
- Fixed an issue where WeConfig would fail to properly calculate upgrade steps for WeOS5 devices when a package required a lower version for which not all platforms were supported.

9. WeConfig 2.1.1 Changelog

Changelog

Improvements

- Preselected the primary address when adding the first static address in WeOS4 VLAN configuration.
- Added labels for FRNTv0 M and N ports.
- Ensured aggregates apply in network order.
- Removed the extra space in the FRNTv2 title bar.
- Improved formatting in the Password Update Needed dialog.

Bugfixes

- Fixed an issue where duplicate port definitions from WeOS devices would prevent WeConfig from processing LLDP information.
- Fixed an issue in the handling of reading existing ports from WeOS devices running 5.25.0 through 5.26.1.
- Fixed an issue that resulted in faulty calculation of WeOS4 upgrade steps.
- Fixed an issue where the Communication Summary did not update properly when opening it with a device preselected.

10. WeConfig 2.1 Changelog

Highlights

- Automatic [Firewall Rule Generator](#)¹
- User defined [Report Builder](#)²
- Unified [Discovery](#)³ page
- New [Route visualization](#)⁴
- [VRRP](#)⁵ configuration
- [Alarm](#)⁶ configuration
- Improvements to [VLAN](#)⁷ configuration
- Added support for [License Keys](#)⁸

Changelog

Backstage Menu

- Moved firmware tab to the About page

Context Menu

- Added Context Menu to Import Backup configuration onto a device
- Added Context Menu to Edit FRNT Ring

Device Access

- Allow overriding used SNMP port and timeout

Device List

- Added secondary version and bootloader version

Diagnostics

- Hover-legend is now scrollable for large amount of devices
- Added time-scale zooming

Discovery

- Merged Interface based and IP-Range based discovery into one view
- Can now set Auth as part of the discovery process
- Added proxy-ssh via known devices
- Moved creation of Link-Local into adapter settings
- Physical network view gets focus on completed device discovery

Firewall

- Added firewall rule generator
- Added firewall advisories
- Added new tab: Conntrack

¹<https://docs.weconfig.westermo.com/Interface/Navigation/Configuration/Firewall>

²<https://docs.weconfig.westermo.com/Interface/Navigation/Support/Reports>

³<https://docs.weconfig.westermo.com/Interface/Navigation/Discovery>

⁴<https://docs.weconfig.westermo.com/Interface/Navigation/Visualization/Topology#topology-route-vis>

⁵<https://docs.weconfig.westermo.com/Interface/Navigation/Configuration/Routing/VRRP>

⁶<https://docs.weconfig.westermo.com/Interface/Navigation/Configuration/Alarm>

⁷<https://docs.weconfig.westermo.com/Interface/Navigation/Configuration/VLAN>

⁸<https://docs.weconfig.westermo.com/Interface/DocumentPanel#doc-status-license>

- Can create rules from Conntrack entry
- Added option to merge rules if possible
- Firewall configuration is now serialized to the WeConfig project
- Added horizontal scrollbars

Firmware Upgrade

- Shows the order devices will be updated (based on chosen algorithm)
- Added option to stop on first fail
- Changed “Choose” icon to “Checkmark” icon
- Added a search-box for filtering devices
- Allowed step calculation to use the optimized ‘all’ command when possible.

Licensing

- Added support for License Keys
- Changed license text from Active/Expired/Inactive to Pro/Basic

Navigation Tree

- Moved “Device Discovery” to top level in the navigation tree
- New text and icons for Favorites

New Devices

- RedBox

New Views

- HSR/PRP
- VRRP
- Alarm

Notifications

- The badge is now hidden when 0 notifications are available
- Security advisories are no longer notifications (they can now be found under Issues)
- Flag color changes depending on type of notification

Physical Network

- New route visualization
- Added button to export topology as PNG
- Increased the horizontal size of the zoom slider
- Added options for Auto Layout to control how spread out the devices are placed
- Added option to hide subnets with only one device
- Performance: Made a better implementation of GetEnumerator for subnet
- Performance: Improved RouteBuilder

Port Protection

- Added a button to restore “Disable Unused” clicks

Port Ingress / Egress

- Changed the active ingress/egress display rate to be in bits-per-second rather than bytes-per-second

Project Template

- Topology is centered on devices after build
- Added option to use existing backups when exporting
- Added option to verify version when importing
- Performance: Build Network From Template is faster and requires fewer temporary ip addresses

Recent projects

- Added preview thumbnails

Reports

- Have been entirely reworked, allowing users to create their own report templates.
- Added default report templates for common use-cases, matching preexisting reports.
- Report previewer is gone, prints directly to PDF.

Route Table

- WeConfig can now display the local PC's route table.
- Added button to auto-refresh route-table.
- Route Table serialization has been improved for better accuracy and compatibility with various WeOS versions.

Settings

- Clarified diagnostic log history setting
- Added configurable ping timeout
- Added network concurrency limit setting
- Added SNMP port and timeout settings
- Edited but unsaved settings now has a colored border

Syslog

- Added error message if the computer's firewall is blocking incoming syslog messages

Traceroute

- Devices are now highlighted when selected by traceroute

Traps

- Added error message if the computer's firewall is blocking incoming trap messages

UI

- Added manual close button to popups
- IP boxes now allow leading 0's
- Expander now looks better in Light Mode
- Added a dedicated CIDR input box

VLAN

- Changed address fields to use a CIDR component (was free text before)
- Added button to add VLAN to all selected devices
- Ports are now expanded by default
- Added separators in the port list for visual clarity
- Show a warning if the VLAN is blocked by the firewall
- Aggregated ports can now be configured by clicking their child-ports

WeOS Versions

- Added WeOS 5.26 specific CLI parsing

Bugfixes

- Resolved an issue where the OSPF protocol was parsed as Any in the firewall
- Resolved an issue in Firmware Upgrade where the “Download now” button did not display error messages
- Resolved an issue in Firmware Upgrade where the “Download now” progress text would show text from all downloads
- Resolved an issue with null-references in ApplicationDiagnostics
- Resolved an issue with null devices in a subnet
- Resolved an issue with null-references when selecting a route
- Resolved an issue where LLDP-frames could cause issues when trying to add a connection
- Resolved an issue where WeOS5 Radius Support was not showing
- Resolved an issue where Automatic Firmware settings didn’t respond to apply properly
- Resolved an issue where SNMP settings didn’t load from old project files
- Resolved an issue to add safety checks to make sure DeviceIconsCache does not crash
- Resolved an issue where running CLI Scripts in network order sometimes didn’t work
- Resolved an issue where a device’s manufacturer was not always set correctly
- Resolved an issue where a device’s temperature was not set correctly on WeOS4 devices
- Resolved an issue where descriptions in the issue list didn’t linebreak properly
- Resolved an issue where port selection in RiCo used too small dropdowns
- Resolved an issue where removing SNMP from a VLAN would delete all SNMPv3 users
- Resolved an issue where old backups could not be imported
- Resolved an issue where locking the topology did not affect subnet- or ring dragging
- Resolved an issue where automatic firmware download did not stop ongoing downloads when changing to “never”
- Resolved an issue where manually added devices did not get properly overridden when something is discovered on their IP address
- Resolved an issue where WeConfig sometimes would freeze during Firmware Upgrade
- Resolved an issue where it was not possible to change tagging of Aggregated ports in VLAN configuration
- Resolved an issue where some versions of WeOS did not report ports correctly

11. WeConfig 2.0.3 Changelog

Changelog

Improvements

- Improved visual indication of Diagnostic log settings.

Bugfixes

- Resolved an issue with password protected files that prevented WeConfig from opening them when the first zip entry was not protected.
- Resolved an issue that caused some settings to to show that they had been applied in the backstage settings view.

12. WeConfig 2.0.2 Changelog

Changelog

Improvements

- Limited the available Authentication and Privacy methods available for selection in Device Access / SNMP to those actually supported by the device, when it is known.

Bugfixes

- Resolved an issue with SNMPv3 communication that prevented WeConfig from communicating with certain devices.
- Resolved an issue that caused WeConfig to crash when a device presented with an IPv6 address and an IPv4 netmask.

13. WeConfig 2.0.1 Changelog

Changelog

Improvements

- Forced IPConfig-based discovery to run SNMP to obtain more WeOS4 information.
- Adjusted margins of the “Availability Status” column in the device list for better alignment.
- Improved WeConfig’s ability to detect port types on WeOS 5.
- Adjusted the way WeConfig detects if two devices are the same to avoid an issue with alternating host-key post firmware-upgrade.
- Ensured that the Settings page is scrollable when the window is too small to contain all settings.

Bugfixes

- Resolved an issue where MRD’s and BRD’s did not behave well during Basic Setup.
- Resolved an issue with FRNTv2 Deserialization from old project files.
- Resolved an issue that caused duplicate firmware upgrade steps to occur when upgrading past 5.21.1 and 5.22.x.
- Resolved an issue where updating the network topology too quickly in succession caused a crash.

14. WeConfig 2.0 Changelog

Updated Graphical User Interface

Dark Mode Support

- Introduced support for dark mode.

Dockable Elements

- Enabled docking for all panels and elements.

Enhanced Selection Mechanics

- Reworked the way that WeConfig handles selection, “Add” and “Clear” buttons have been removed in favor of directly matching the selection in Physical Network / Devices.

New Panels

Discovery

- Interface-Based Device Discovery: Relocated from the top bar to its own panel.
- ICMP Ping Discovery: Relocated from the top bar to its own panel.

Configuration

- Firewall: Introduced a new firewall configuration panel.
- Routing/OSPF: Licensed feature. Provides detailed OSPF configuration for devices.
- Routing/Static: Licensed feature. Allows configuration of specific static routes.
- Aggregates: Enables LACP configuration.

Per-Device Views

- Route Table: Relocated from the Selected Device section.
- Properties: Relocated from the Selected Device section.
- Attachments: Relocated from the Selected Device section.
- Configuration Files: Relocated from the Selected Device section.
- Cellular: Relocated from the Selected Device section.

Maintenance

- Clone or Replace Device: Replaces the Paste and Replace function.

Support

- Issues: Collects and displays application and device issues.

Reworked Panels

Network Visualization

- Physical Network: Includes Layer 3 visualization, updated connection colors, ribbon controls, new indicators, and new context menu options.
- Devices: Removed Backup, Bootloader, MAC, and other columns.

Configuration

- Accounts: Reworked to represent the configuration of user accounts on the device, not just admin password configuration.
- VLAN: Merged tabs into a matrix view.
- System/SNMP: Now a Staged Task.

- System/Logging: Now a Staged Task.

Maintenance

- Firmware Upgrade: Now a Staged Task.
- Device Access Settings: Allows editing of the username and PKI usage. Test connection now also tests SSH, SNMP, and HTTP(S) reachability.
- CLI Scripts: Renamed from “CLI”.

Diagnostics

- Diagnostics: Uses a new charting framework. Measurements are split per unit. Select measurements, rather than device/measurements.

Support

- Help: Now links to the user guide.
- Release Notes: Now links to the relevant changelog.
- Reports: Now a licensed feature. Is now a panel and includes a progress log.

Tools

- SHDSL Reach Calculator: Uses a new charting framework.

Project Template

- Export from Current Project: Now a Staged Task.
- Build Network from Template: Now a Staged Task.

Changelog

- Accounts (previously passwords) now have a quick-button for generating and copying a public/private key pair to the clipboard.
- “On approval” is now the default update option.
- Added “Never” as an update option.
- Added Dark mode and system theme.
- Added Discovery Neighbours as a discovery option to both ICMP and interface-based discovery.
- Added Expand/Collapse functionality to physical network.
- Added Opacity Controls to physical network.
- Added a periodic ping check that tries to reach devices in the project.
- Added a search box to physical network.
- Added actual toast for notifications.
- Added an icon to physical network that indicates that a firmware upgrade is available for the device.
- Added backstage menu..-----
- Added context menu options for RIP, OSPF, and static routes.
- Added favorites list.
- Added firewall configuration panel.
- Added full docking layout handling.
- Added icons to all panels.
- Added observable ingress/egress rates to Configuration/Ports/Ethernet.
- Added read support for HSR-PRP and redbox.
- Added spinners to clickable links.
- Added static route configuration.

- Added licenses for unlocking/locking features, with an option for temporary trial licenses built into the software.
- Added the ability for WeConfig to proxy SSH connections via WeOS devices.
- Added the ability to download missing firmware directly in Firmware Upgrade.
- Added the ability to edit manually edited connections.
- Added the ability to mirror device locations across X/Y axis in physical network.
- Added the ability to remove FRNT rings.
- Basic setup now allows empty host names.
- Connection colors have been updated to match with other Westermo resources.
- Deleted Configuration Baselines panel.
- Deleted Configuration Manager panel.
- Deleted logical network.
- Device access: For devices supporting PKI authentication, PKI authentication can now be enabled or disabled.
- Device properties now contain hardware revision when applicable.
- Devices, sorting by IP address now sorts numerically rather than alphabetically.
- Diagnostics now only need to select measurements, not measurements per device.
- Discovery: When detecting an unknown device through LLDP, WeConfig will now add its known port information to the device.
- Dropped support for project files of versions lower than 3.0.
- Fixed a bug involving reading SFP diagnostics.
- Fixed a bug where 192.168.2.200 would remain configured on WeOS 4 devices after basic setup was complete.
- Fixed a bug where local firmware files occasionally would not show up in Firmware Upgrade.
- Fixed an issue with “fill” zooming where it hid the top icons on devices.
- Fixed an issue with the RedFox family occasionally being considered as incompatible with WeOS 4.33.2.
- Fixed an issue with the devices list where the Refresh context menu option was occasionally not present.
- Fixed issues with FRNT configuration.
- FRNT Configuration: Focal point is now indicated.
- FRNT Configuration: Selecting a device now selects it in the topology/devices.
- Improved performance of LLDP frame receiver.
- Improved the performance of Project file Loading and Saving.
- Improved the performance of many WeOS5 associated operations.
- Made navigation menu collapsible.
- Merged communication summary and communication details into one view.
- Merged firmware download settings and firmware download status.
- Moved Discovery into separate panels.
- Moved Project Gold file into separate panels.
- Moved Reports into a panel.
- Moved unreachable device notifications to issues.
- Moved to Velopack as installer.
- New startup screen.
- Notification badge color now reacts to the intensity of notifications.
- Prevented PC from going to sleep during a firmware upgrade sequence.
- Prevented downgrade of WeOS bootloader below barebox 2017.12.0-6.

- Rearranged VLAN editing interface.
- Reworked Firmware Upgrade into a Staged Task.
- Reworked Logging configuration into a Staged Task.
- Reworked SNMP configuration into a Staged Task.
- Rings are now rendered in physical network and can be selected / dragged.
- Reset layout button added to backstage.
- Split "Selected device" into multiple panels.
- Split "selected device" into multiple different panels.
- Subnets are now rendered in physical network and can be selected / dragged.
- Text in communication summary/details is now copyable.
- The "CLI" panel has been renamed to "CLI Scripts".
- Unified list views across many panels to have a similar look and feel.
- Updated DSL connection visualization.
- Updated General log to improve performance and appearance.
- Updated project serialization to version 3.1.
- Updated target runtime to .NET 9.
- Updated how unknown devices are rendered in the topology when their MAC is a known OUI.
- WeConfig now remembers the last selected interface if it is disconnected and then reconnected.
- WeConfig will now prompt the user for trust when attempting to send non-factory-defaulted credentials to a device with an unknown/unrecognized host key.

